



Datasheet Serie X200

Special Features:	Blindscan:	5MHz, 4MHz, 3MHz, 2MHz, 1MHz
	Channels:	10000
	Unicable	available
	MOSAIC	2x2, 3x3
	PIG	Picture and Sound in Menu
	Color:	black or silver
System:	Prozessor:	STi5119, 200Mhz
	Flash:	2 Mb
	SDRam:	16 Mb
	EEProm:	32 Kbyte
Smartcardreader:	2 Smartcardreader. (Optional)	per Conax and Xcrypt
CI Slots:	2CI Slots (Optional)	
Tuner:	Input symbol Rate:	2-45 MS / s
	Frequency Range:	950-2150 MHz
	Signal Level:	-25 - -75 dBm
	LNB Power/Polarisation:	Vertikal: +13V, Horizontal: +18V
	Stream:	max. 400mA, 22 KHz: Frequenz: 22 KHz
	Amplitude:	0,8 +/- 0,2V
	DiSEqC:	1.0,1.1, 1.2, USUALS
Audio/Video Decoder:	Transport Stream:	MPEG-2 ISO
	Video Formats:	4:3 & 16:9
	Resolution:	720x576 (PAL)
	Audio:	MPEG/ Layer 1&2
Display:		7 Segment Display
Connectors:	Tuner & LNB:	IEC169, F-type, female
	RCA:	Stereo Output, L/R
	Scart:	Input / Output
	Data:	RS232C Interface
	S/PDIF:	optical
	0/12V:	RCA / Cinch type

	RF Modulator :	RFConnector, 75ohm
Power Supply:	Input Voltage:	90-245V, 50-60Hz
	Power Consumption:	max. 25W
Specifications:	Weight:	2Kg
	Dimensions	(W x H x D): 30x21x6,2 cm